

## The World of Color...It's CASIO's Solution!

Advanced technology with stylish modern design  
to fit your business

TE-3000S

TE-4000F

TE-4500F

Electronic Cash Register with Color Backlight Display



TE-4000F

**5**-color backlight LCD screen

TE-3000S

TE-4000F

TE-4500F

# Equipped with a full range of advanced features to complement and expand your business

## Highlighted Features

### System configuration

A maximum of 32 terminals can be connected to consolidate sales data. Shared check tracking by up to 4 terminals and printer sharing of up to 3 external printers can also be connected. Links among terminals can be set up easily using CAT5 or CASIO inline cables. (Optional Arc-net communication board required.)

### Operator display

5.2-inch LCD with 2 x 16 characters ensuring the operator a clear view of all transaction information. 10-digit, 7-segment display space for numeric entries. 5-color backlight enabling the operator to select a display illumination color to suit the store image. Scheduler function permitting switching among both backlight colors and menu levels to differentiate items or prices (between Lunch and Dinner menus, for example).



### Tilt screen operator display

Tilt screen function allowing the operator to adjust the display to the optimal angle for comfortable readability.



### Printer

Fast, silent 58mm thermal receipt and journal printer with fast line printing. Receipt auto cutter installed. Drop-in paper loading for easy paper roll handling. Graphic/watermark logos presenting an affluent image.



### Data storage

CF (Compact Flash) card interface for data back-up and restore installed as standard equipment.



### Serial ports

3 x RS232c ports for direct communication with, modem, barcode scanner, external printer and slip printer. Com2 with +5v power provided for optional HHS-15 barcode scanner.



### Scanning

Barcode scanning for quick, accurate registration available with optional barcode reader.

### Keyboards

TE-3000S: raised keyboard; TE-4000F: combination keyboard with reversible flat keyboard; TE-4500F: full flat keyboard (TE-4500F availability limited to certain regions.)

## Reports

- Financial
- Transaction
- Department, sub-department
- PLU
- Table analysis
- Open check
- Monthly
- Hourly, hourly item
- Employee (time and attendance)
- Flash
- Group
- Clerk
- Scanning PLU
- Mix & match
- Not-found PLU

Z	10-10-2010(SUN) 21:10	Mode symbol/date/time
K. SMITH	MC#01 000045	Clerk descriptor/Mc-No./consecutive No.
Z	SCAN PLU	Report header/title/reset counter(Z only)
	0001	Report code
	2001026	Report code
DEPT01	.....01	Classified title(by group/dept/sub-dept)
SCAN_PLU001	382	Scanning PLU character/quantity
17.07%	-1,583.47	Sales ratio/total
#4901234567894		Scanning PLU code
SCAN_PLU002	382	
38.01%	-3,526.46	
#4989012345674		
SCAN_PLU003	382	
10.49%	-973.45	
#4967890123454		
	1253	Total of this classification
	-9,275.83	
DEPT02	.....02	
SCAN_PLU010	453	
	-1,583.47	
#4945678901234		
	243	
	-10,375.93	
TL	12653	Quantity total
	-273,375.93	Amount total

## Options

Model No.	Product
RK-3	1MB memory module
I/O-PB-17	Arc-net communication board
UP-250	External impact printer
UP-350	External thermal printer
SP-1300	Slip printer
HHS-15	Hand-held barcode scanner

## Specifications

Displays	Operator	5.2-inch LCD with color backlight 2 x 16 characters / 10 digits, 7 segments
	Customer	Pop-up 10-digit numeric LED
Printer	Printing method	Two-station thermal printer
	Printing speed	20 lines/sec. (max.)
	Paper width	58mm +0/-1mm x 83 φ
	Receipt auto cutter	Yes
	Paper-loading	Drop-in paper-loading
Memory backup		90-day data back-up (vanadium lithium battery)
Power consumption	AC 120V	Operating 0.9A, Standby 0.2A
	AC 230V	Operating 0.5A, Standby 0.11A
Operating environment	Temperature	0 to 40 °C
	Humidity	10 to 85%RH
Dimensions (W x D x H)		410 x 491 x 215(292)*mm
Weight		Approx. 9 kg

\*Includes pop-up customer display height.



<http://world.casio.com>

NOTE: Specifications and design subject to change without notice.

**CASIO**  
CASIO COMPUTER CO., LTD.  
Tokyo, Japan